

SAS DRY-BREAKS

The new generation of eco-friendly Dry Breaks!



ADVANTAGES

- ▶ Excellent transfer rates
- ▶ Minimal spill upon separation
- ▶ Emission control for volatile chemicals
- ▶ Easy to use
- ▶ Prevention of product mix-up

It can be used in the following industries:

- ▶ Transport
- ▶ Oil & gas
- ▶ Energy (including offshore & green energy products)
- ▶ Chemical (including urea)
- ▶ Food production
- ▶ Pharmaceutical

Specifications

Sizes:	1" - 4"
Connections:	BSP/NPT/Flanged
Materials:	Stainless Steel, Aluminium
Seals:	Viton and others on request
Suitable for:	Water/Chemicals/Petroleum and oil products
Certified to:	NATO STANAG 3756

Extensive industry experience led to the all new SAS coupling designed for safe and effective fluid or gas transfer.

SAFE, AFFORDABLE, SIMPLE.



SAS Part Number Details



SAS T 070 20 B AL V

RANGE	UNIT TYPE	THREAD SIZE		BODY		SEAL																		
	T Tank Unit (Adaptor) H Hose Unit (Coupler) C Dust Cap P Dust Plug	10 1" 15 1.5" 20 2" 25 2.5" 30 3" 40 4"	AL Aluminium SS Stainless Steel		V Viton® E EPDM B Buna																			
	PRODUCT SIZE	THREAD TYPE																						
	<table border="0"> <tr> <td></td> <td>D (Front)</td> <td>DN (Nominal)</td> </tr> <tr> <td>056</td> <td>56mm</td> <td>25mm</td> </tr> <tr> <td>070</td> <td>70mm</td> <td>40mm</td> </tr> <tr> <td>105</td> <td>105mm</td> <td>65mm</td> </tr> <tr> <td>119</td> <td>119mm</td> <td>80mm</td> </tr> <tr> <td>164</td> <td>164mm</td> <td>100mm</td> </tr> </table>		D (Front)	DN (Nominal)	056	56mm	25mm	070	70mm	40mm	105	105mm	65mm	119	119mm	80mm	164	164mm	100mm	B BSP Female N NPT Female F Flanged ANSI 150				
	D (Front)	DN (Nominal)																						
056	56mm	25mm																						
070	70mm	40mm																						
105	105mm	65mm																						
119	119mm	80mm																						
164	164mm	100mm																						